Dell® Latitude® LM
Documentation Update

This document updates information contained in the online *Dell Latitude LM User's Guide* and the *Dell Latitude LM Reference and Troubleshooting Guide*.

New Microprocessor Options

The Dell Latitude LM is now available with a 166-megahertz (MHz) or 133-MHz Intel® Pentium® microprocessor with MMX™ technology.

Current application programs not designed specifically for MMX technology should have a small improvement in performance when run on a system with a Pentium microprocessor with MMX technology. Software written specifically to take advantage of MMX technology (which will be labeled "Designed for Intel MMX") will have a greater improvement in performance, depending on the type of application program.

The Pentium microprocessor with MMX technology has twice the internal cache memory (32 kilobytes [KB]) as the standard Pentium microprocessor.

To see the technical specifications of the new microprocessors, search on "microprocessor specifications" in the online *System User's Guide*. The online guide is in the Dell Accessories folder or program group.

New Memory Module Support

The Dell Latitude LM now supports 32-megabyte (MB) memory modules. With the 8 MB of standard non-removable memory on the system board and two 4-MB memory modules standard with every Latitude LM, the computer now supports a maximum of 72 MB of system memory. The following memory module combinations are possible:

- 24 MB — Install two 8-MB memory modules.
- 40 MB — Install two 16-MB memory modules.
- 72 MB — Install two 32-MB memory modules.

New Memory Specifications

The Dell Latitude LM now supports extended-data out (EDO) memory. EDO memory technology improves performance over fast-page-mode technology by using a shorter page-mode cycle time while accessing data within a single page of memory. See the following table for the updated memory specifications.

Memory	
Architecture.	EDO
Memory module capacities.	4, 8, 16, and 32 MB; must be installed in matched pairs (two 4-MB modules, two 8-MB modules, two 16-MB modules, or two 32-MB modules). Both EDO and fast-page-mode modules are supported in matched pairs.
Standard RAM	16 MB; 8 MB on system board and two 4-MB EDO memory modules installed
Maximum RAM . . .	72 MB
Memory access time:	
tRAC	60 ns
tCAC	15 ns
BIOS address	F000:0000

NOTE: For the full name of an abbreviation or acronym used in this table, see the Glossary in the online System User's Guide.

New Video Controller

The Dell Latitude LM's standard video subsystem now includes 1.1 MB of video memory. For more information about new video modes and resolutions, see "Using the Display," or search on "text modes" and "graphics modes" in the online *System User's Guide*.

To see the technical specifications of the new video subsystem, search for "video specifications" in the *System User's Guide*. The online guide is in the Dell Accessories folder or program group.

Setup Program Changes

The following information updates Chapter 2, "Customizing System Features," in the *Reference and Troubleshooting Guide*:

- The default setting for the **AC POWER SAVE** option in the Power menu is **OFF**.
- The **ALARM RESUME TIME** option in the Power menu tells the computer an exact time to resume normal operation when it is in suspend mode.



* *On the Dell Latitude LM, a CD-ROM drive installed in the options bay is recognized as IDE Drive 1.*

Figure 1. Main Screen of the Dell Diagnostics

Dell Diagnostics Changes

This section updates Chapter 4, "Running the Dell Diagnostics," in the *Reference and Troubleshooting Guide*.

Main Screen

The main screen of the diagnostics (see Figure 1) has been revised to show more detail in the System Configuration area.

Test Limits Under Main Menu Options

In the Test Limits option, press the <PAGE DOWN> key to select the next menu or submenu in the Test Limits category. Press the <ESC> key to return to the main Test Limits menu.

USB Subtests Added

The following subtests have been added to the System Set Test Group. These subtests run only if the computer has a Universal Serial Bus (USB) connector.

- The USB Register Test checks the onboard registers of the USB interface. This subtest does not test USB peripherals.
- The USB Memory Structure Test monitors the ability of a USB controller to process a simple set of memory-resident instructions.

Getting Help

Many of the telephone numbers in Chapter 5, "Getting Help," of the *Reference and Troubleshooting Guide* have changed.

Use the most up-to-date numbers, which are in the "Calling Dell" section of the online *System User's Guide*. The *System User's Guide* is in the Dell Accessories folder or program group.

© 1997 Dell Computer Corporation. All rights reserved. Printed in the U.S.A.
Information in this document is subject to change without notice.

Trademarks used in this text: *Dell*, the *DELL* logo, and *Latitude* are registered trademarks of Dell Computer Corporation; *Intel* and *Pentium* are registered trademarks and *MMX* is a trademark of Intel Corporation. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell Computer Corporation disclaims any proprietary interest in trademarks and trade names other than its own.